

| DEVICE TYPE | MIL-S-19500/ | V _{CBO} VOLTS | V _{CEO} VOLTS | I _C (CONT.) AMPS | POWER (@T _C = 25°C) WATTS | CASE TYPE | CHIP TYPE |
|---------------------|--------------|------------------------|------------------------|-----------------------------|--------------------------------------|-----------|-----------|
| 2N2880 JAN, TX, TXV | 315 | 110 | 80 | 5.0 | 30* | TO-111 | 184 |
| 2N3418 JAN, TX, TXV | 393 | 85 | 60 | 5.0 | 15* | TO-5/39 | 185 |
| 2N3419 JAN, TX, TXV | 393 | 125 | 80 | 5.0 | 15* | TO-5/39 | 185 |
| 2N3420 JAN, TX, TXV | 393 | 85 | 60 | 5.0 | 15* | TO-5/39 | 185 |
| 2N3421 JAN, TX, TXV | 393 | 125 | 80 | 5.0 | 15* | TO-5/39 | 185 |
| 2N3439 JAN, TX, TXV | 368 | 450 | 350 | 1.0 | 5 | TO-5/39 | 100 |
| 2N3440 JAN, TX, TXV | 368 | 300 | 250 | 1.0 | 5 | TO-5/39 | 100 |
| 2N3740 JAN, TX, TXV | 441 | -60 | -60 | -4.0 | 25 | TO-66 | 269 |
| 2N3741 JAN, TX, TXV | 441 | -80 | -80 | -4.0 | 25 | TO-66 | 269 |
| 2N3749 JAN, TX, TXV | 315 | 110 | 80 | 5.0 | 30* | TO-111/I | 184 |
| 2N3846 JAN, TX | 412 | 300 | 200 | 20.0 | 150* | TO-63 | 114 |
| 2N3847 JAN, TX | 412 | 400 | 300 | 20.0 | 150* | TO-63 | 114 |
| 2N3902 JAN, TX | 371 | 700 | 400 | 3.5 | 100** | TO-3 | 142 |
| 2N3996 JAN, TX, TXV | 374 | 100 | 80 | 5.0 | 30* | TO-111/I | 184 |
| 2N3997 JAN, TX, TXV | 374 | 100 | 80 | 5.0 | 30* | TO-111/I | 184 |
| 2N3998 JAN, TX, TXV | 374 | 100 | 80 | 5.0 | 30* | TO-111 | 184 |
| 2N3999 JAN, TX, TXV | 374 | 100 | 80 | 5.0 | 30* | TO-111 | 184 |
| 2N4150 JAN, TX, TXV | 394 | 100 | 70 | 10.0 | 5* | TO-5 | 185 |
| 2N4865 JAN, TX, TXV | 380 | 100 | 80 | 50.0 | 350 | TO-114 | 196 |
| 2N5157 JAN, TX | 371 | 700 | 500 | 3.5 | 100** | TO-3 | 142 |
| 2N5237 JAN, TX, TXV | 394 | 150 | 120 | 10.0 | 5* | TO-5 | 185 |
| 2N5238 JAN, TX, TXV | 394 | 200 | 170 | 10.0 | 5* | TO-5 | 185 |
| 2N5250 JAN, TX, TXV | 380 | 125 | 100 | 50.0 | 350 | TO-114 | 196 |
| 2N5251 JAN, TX, TXV | 380 | 180 | 150 | 50.0 | 350 | TO-114 | 196 |
| 2N5415 JAN, TX, TXV | 485 | -200 | -200 | -1.0 | 10 | TO-5/39 | 200 |
| 2N5416 JAN, TX, TXV | 485 | -350 | -300 | -1.0 | 10 | TO-5/39 | 200 |
| 2N5664 JAN, TX, TXV | 455 | 250 | 200 | 5.0 | 30* | TO-66 | 140 |
| 2N5665 JAN, TX, TXV | 455 | 400 | 300 | 5.0 | 30* | TO-66 | 140 |
| 2N5666 JAN, TX, TXV | 455 | 250 | 200 | 5.0 | 15* | TO-5 | 140 |
| 2N5667 JAN, TX, TXV | 455 | 400 | 300 | 5.0 | 15* | TO-5 | 140 |
| 2N6306 JAN, TX, TXV | 498 | 500 | 250 | 8.0 | 125 | TO-3 | 104 |
| 2N6308 JAN, TX, TXV | 498 | 700 | 350 | 8.0 | 125 | TO-3 | 104 |
| 2N6546 JAN, TX, TXV | 525 | 850 | 450 | 15.0 | 175 | TO-3 | 105 |
| 2N6547 JAN, TX, TXV | 525 | 650 | 350 | 15.0 | 175 | TO-3 | 105 |

*T_C = 100°C in lieu of 25°C

**T_C = 75°C in lieu of 25°C